

Customisable table-top kit with 2xUSB charger, 3 German socket outlets and 1 empty element aluminium Simon 400

REF. 42523000-133



BASIC INFORMATION

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

1

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

NOMINAL VOLTAGE (V~)

250 V~

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9006

NUMBER OF REAR ENTRANCES

1

NUMBER OF SOCKETS

3 sockets for standard current circuit

NUMBER OF USB CHARGERS

1

VERSION

5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE

Suitable for fixing to furniture.

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208106

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.15

PRODUCT NET WEIGHT

2.15

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053208106

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

195

PACKAGING LENGTH

320

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5616000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.15

PACKAGING WEIGHT UNIT

KGM