

Flat voice and data plate with dust cover for 1 element with 1 category 5e UTP RJ45 white Simon 500 Cima

REF. 50004085-030



BASIC INFORMATION

DESCRIPTION

In the Simon 500 Cima series you will find this voice and data plate in white colour finish of the plate, category 5e UTP, includes a dust shutter, in addition to an element with an RJ45 connector. This is the individual version with a module and is available for one or two connectors. If you want to incorporate this plate of voice and data in columns horizontal or vertical enclosures, the clips for this are included. This means that you have to use any type of external adapter, or screws. Its measures are 50 compact x 50 x 32.5 millimetres and requires a wire cross-section 22-26 AWG. Its manufacturing commitment components isolated thermoplastically and halogen-free. This is achieved to increase security in the room in which it is using, even at high temperatures. The plates of the Simon 500 Cima series support very variable temperature, up to a maximum of + 60 degrees centigrade and maintenance of the same is very simple.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

1

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053098042

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.026

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.52

PRODUCT NET WEIGHT

0.026

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

