

Linear luminaire 6100 BT Mesh 31W 4000K with detector 24GHz 8m HF+LUX and emergency IP65

REF. 89364620-314



BASIC INFORMATION

DESCRIPTION

Watertight luminaire with integrated HF detector, emergency function and Bluetooth connectivity. Power is 42.4 W, luminous flux is 4525 lm and colour temperature is 4000 K. Emergency mode duration is 3 h in accordance with EN 60598-2-22. Maximum installation height is 4 m, surface-mounted. Detection range is 8 m and detection angle is 360°.

The light-level adjustment range is 2 - 2000 lux and the timing range is 5 s - 60 min. The luminaire is configured via a Bluetooth app. Luminaires can be interconnected via Bluetooth mesh.

Supply voltage is 220 - 240 VAC. Operating temperature: -20 - 40 °C.

Protection rating IP 65 and IK 08. Dimensions: 1200 x 90 x 80 mm.

5-year warranty.

For more product information, visit the STEINEL website by clicking [here](#)

FINISH

Grey

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

IP RATING

IP65

CONTROL

BT

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053465936

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053465936

PACKAGING VOLUME

26676000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

95

PACKAGING GROSS WEIGHT

3.95

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

180

PACKAGING NET WEIGHT

3.38

UNITARY PACKAGING GROSS WEIGHT

3.72

PACKAGING LENGTH

1560

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

3.38