

Extension 0.5 metres for aluminium column with 4 sides Simon K45

REF. ALK54P05/8



BASIC INFORMATION

DESCRIPTION

0.5 metre extension for 4-sided aluminium pole from the Simon K45 range. Is fixed to the floor and its dimensions are 500 x 125 x 125 mm debes to know that to be fully effective, it is only possible to combine one extension per pole. This extension is made in anodised aluminium and has been designed in accordance with the regulation UNE-EN 50.085-2-4-: 2006, so that it is a model that complies with all the guarantees. It can be installed in rooms with a temperature which is located between -25 and the most of 120 ° C, so it is ideal for use in any type of climatology. You just need a soft, dry cloth to clean this extension for the pole from the Simon K45 range, as well as forget of any cloth and / or abrasive cleaner with chlorine for cleaning since you could have damage the extension and make this does not operate the most appropriate.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

VERSION

4-sided

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using connecting pins

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050600

PRODUCT NET WEIGHT

2.615

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

19251000

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436050600

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

135

PACKAGING NET WEIGHT

2.615

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

2.615

PACKAGING LENGTH

920