

Flush-mount trim cover for adjustable floor box or service cover 6 elements grey Simon 500 Cima

REF. 52053103-035



BASIC INFORMATION

DESCRIPTION

The box for 2 elements in grey colour belonging to the Simon 500 Cima series adjustable floor and for 2 elements, in addition, it is specifically designed for installation in concrete floor, although it may also be carried out in raised floor. Not be installed in the same floor lining, the piece of 132x187x76 optionally, it can be combined with the flush-mount trim cover. Also features a perfect finishes in grey, insertion by cutting (1 click ® and is compatible with elements up to 250 Volt voltage and 16 Ampere current. Also, it is made of metal components with thermoplastic insulation coated self-extinguishing halogen-free, to ensure that is no flame spread in case of fire, and a very low toxicity in the event of smoke generation. Our brand guarantees the highest quality through the perseverancia and innovation in its products, and that is that the collection Simon 500 Cima get the bond between the best mechanisms functional on the market and the maximum security.

FINISH

Grey

PACKAGING CONTENTS

Trim cover

MATERIAL

Plastic

ETIM CLASS

EC002417

REMARKS

Optional element. To combine with the floor box if not installing the same floor finish.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IK CLASSIFICATION

08

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6, 8 and 12 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

6 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP4X

RAL

7011

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

KIT AVAILABILITY

No

VERSION

6 elements

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

INSTALLATION DIRECTION

Horizontal, Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.111

PACKAGING LENGTH

170

UNITARY PACKAGING WIDTH

0

PRODUCT NET WEIGHT

0.111

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3.217

UNITARY PACKAGING
MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053101520

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

75

PACKAGING NET WEIGHT

1.11

PACKAGING WIDTH

165

PACKAGING WEIGHT UNIT

KGM

