

Monobloc kit for 1 element with 1 push-button switch and 1 USB charger 2.1A aluminium Simon 270

REF. 27191610-093



BASIC INFORMATION

FINISH

Aluminium

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC002949

MATERIAL

Plastic,Metal

PACKAGING CONTENTS

Mechanisms, frame+cover,
frame-holder and instruction
sheet

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 10 AX	OPERATING TEMPERATURE RANGE (°C) 5 - 45 °C
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	IP RATING IP20	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
NUMBER OF POSSIBLE ELEMENTS Monoblock	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	USB CURRENT (A) 2,1 A
FORMAT USB	TYPE OF MECHANISM Push Insertion	USB VOLTAGE (V~) 127/230 V~
FREQUENCY 50 - 60 Hz	MONOBLOCK Yes	VERSION Monoblock
INDICATOR FUNCTION No		VOLTAGE (V~) 127/230 V~

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast
	INSTALLATION TYPE Suitable for flush mounting	

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) | EN 50563:2011 | EN 50563:2011 A1:2013 | EN 60669-1:2018 | EN 62368-1:2014 | EN 62368-1:2014 A11:2017 | EN IEC 63000:2018 | ETSI EN 301489-34 V1.4.1 | ETSI EN 301489-34 V2.1.1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053283745

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053283745

PACKAGING VOLUME

921600

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

75

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

96

PACKAGING NET WEIGHT

0.1

UNITARY PACKAGING GROSS
WEIGHT

0.1

PACKAGING LENGTH

128

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.1