

MD-20 180° PIR+LUX wall surface DALI-2 Input white IP54

REF. 89202335-230



BASIC INFORMATION

DESCRIPTION

Surface PIR motion and brightness detector. The recommended installation height is 2.5 m, with a maximum height of 2.5 m. It has a detection angle of 180° and an opening angle of 90°. The tangential detection range is 20 m and the radial detection range is 4 m.

The brightness regulation range is 2 - 1000 lux and the timing range is 5 s - 15 min. The detector configuration is done via DALI.

It has a TEACH operating mode. Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 5 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection rating, and dimensions: 95 x 95 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP54

RAL

9003

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

1.8

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053380789

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.241

PRODUCT NET WEIGHT

0.151

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053380789

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.241

PACKAGING NET WEIGHT

0.151

PACKAGING WEIGHT UNIT

KGM