

# Service cover for 4 elements for installation in concrete or raised floor grey Simon 500 Cima

REF. 52054102-035



## BASIC INFORMATION

### DESCRIPTION

The Simon 500 Cima series presents our kit adjustable floor box for 2 elements whose design has been designed to be recessed in raised floor. The piece measures 132x187x92 mm, an end in graphite finish and is made of metal materials with halogen-free coated self-extinguishing halogen-free thermoplastic to ensure in case of fire that the flame spread, it is not a extremely low toxicity in the event of smoke generation. And it is that, among the values of the brand, is the always offer the highest quality of its products thanks to its constant interest by improve them. This is materialize in its collection Simon 500 Cima, which gives assemble solutions for those who are looking for a total security without renouncing the best mechanisms functional on the market.

### FINISH

Grey

### PACKAGING CONTENTS

Service cover and installation manual

### ETIM CLASS

EC001903

### MATERIAL

Plastic

### REMARKS

Once the product has been installed, you have the option to combine it with the flush-mount service cover (ref.52053102-035) in cases where you do not install the same floor covering.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

### AVAILABLE IN

2, 4, 6, 8 and 12 elements

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

### HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

### INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

### IP RATING

IP4X

### KIT AVAILABILITY

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

### NUMBER OF MODULES

4 modules

### RAL

7011

### RECESS DIMENSION (MM)

170 x 155 mm

### VERSION

4 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 14 and 54 mm

### NUMBER OF COVER OPENING POSITIONS

2

### REMOVAL OF COVER

Only with tool

### EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

### TYPE OF FASTENING

Using fastening claws on the concrete floor tray or the raised floor tile (provided in the service cover)

### CAN BE INSTALLED IN TRAY

Plástica

### INSTALLATION DIRECTION

Horizontal, Vertical

### INSTALLATION TYPE

In raised floor and concrete floor

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053101605

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.775

### PRODUCT NET WEIGHT

0.775

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053101605

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

84

### PACKAGING WIDTH

181

### PACKAGING LENGTH

212

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3.223

### PACKAGING VOLUME UNIT

DMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.775

### PACKAGING WEIGHT UNIT

KGM

