

Danish socket outlet 13A with screw terminal connection 2 elements graphite K45

REF. K15/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation on wall, floor, ceiling, and furniture, and Simon 500 Cima enclosures (requires combining with the adapter from K45 to 500 Cima ref. 50012088-030).

ETIM CLASS

EC000125

TECHNICAL INFORMATION

FORMAT

Danish

IP RATING

IP20

RAL

7021

CURRENT (A)

13 A

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8426436052390

PACKAGING VOLUME
122500

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
50

PACKAGING GROSS WEIGHT
0.414

UNITARY PACKAGING GROSS
WEIGHT
0.041

PACKAGING WIDTH
10

PACKAGING NET WEIGHT
0.32

PRODUCT NET WEIGHT
0.032

PACKAGING LENGTH
245

PACKAGING WEIGHT UNIT
KGM