

PD-40 Large Areas PIR+LUX recessed box Potential Free squared white IP20

REF. 89218829-230



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted presence and brightness detector. The recommended installation height is 2.5 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 40 m and the radial detection range is 8 m.

The brightness regulation range is 2 - 1000 lux and the timing range is 5 s - 15 min. The configuration of the detector is done through potentiometers and remote control.

It features TEACH operating mode. Possibility of interconnection between master/master sensors up to 10 detectors. The control output is potential-free and the switchable power is max 2000W, min 100mA 12V.

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, protection rating IP 20 and dimensions: 94 x 94 x 78 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9003

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

Potential Free

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053380574

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.247

PRODUCT NET WEIGHT

0.157

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053380574

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.247

PACKAGING NET WEIGHT

0.157

PACKAGING WEIGHT UNIT

KGM