

Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6 FTP white Simon 500 Cima

REF. 50003089-030



BASIC INFORMATION

DESCRIPTION

To ensure high speed data transmission in the work area, the flat base plate of voice and data Simon 500 Cima, is the option indicated. With finishes in a simple intense tone White, with dust cover for 1 element (protection against ingress of dust or other elements) and with 2 RJ45 category 6 FPT, as a guarantee of speed and security in your network to the transmission of data. Compatible with Keystone and cabling ports 22-26 AWG, has clips for enclosures horizontal or vertical, it does not need adapter and opens the range of installation possibilities to adapt to the specific needs of each specific space. The simplicity and speed of assembly, it facilitates the integration of the set in a reduced space. Made of halogen-free, self-extinguishing thermoplastic prevents the flame spread and toxicity by smoke in case of fire.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 RJ45 category 6 FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

1

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097885

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.055

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

1.1

PRODUCT NET WEIGHT

0.055

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

