

LANE 1600 linear luminaire 1-10 V HO Surface-mounted 3000 K Batwing Black

REF. 91301108-388



BASIC INFORMATION

BODY MATERIAL

Aluminium

PACKAGING CONTENTS

1 Unit

APPLICATION

Domestic,Office,Retail,Contract

ETIM CLASS

EC001743

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DIRECTIONAL

No

LIGHTING EFFICIENCY (LM/W)

hasta 97 lm/W

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS (LM)

3720 lm

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

I

NUMBER OF LUMINAIRES

1

POWER SUPPLY (V~)

220/240 V~

ENERGY EFFICIENCY

A+

MACADAM STEPS

<3 Step MacAdam

RAL

9005

L70 (°C)

100000h at 25°C

OPTICS

Batwing 105°

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

30000h at 25°C

POWER FACTOR (Φ)

>0,9

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

105°

POWER (W)

50 W

CRI

90

COLOR TYPE

NW

CHROMATICS CRI ICONS

CRI
90

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface-mounted/Suspended

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547033034

PACKAGING VOLUME

16128000

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

3.85

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING WIDTH

84

PACKAGING NET WEIGHT

3.5

PRODUCT NET WEIGHT

3.5

PACKAGING LENGTH

2400

PACKAGING WEIGHT UNIT

KGM