

Voice and data angled plate with dust cover for 1 element and 1 RJ45 connector category 5e UTP aluminium Simon K45

REF. K8095U/8



BASIC INFORMATION

DESCRIPTION

Angled plate of voice and data with dust shutter of 1 element and 1 RJ45 connector of category 5e UTP finished in aluminium. The product measures 45x45 mm and has a depth of 46.5 mm. It is in compliance with the regulation that regulates this type of mechanisms, it consists of metal parts with halogen-free thermoplastic insulation and character self-extinguishing that prevents it from extending the flame in case of fire. The voice and data plate is suitable for surface and flush mounting and allows its integration in vertical enclosures. In this case, it would be necessary to use the 90° positioner (reference K66) so that the plate is maintained aimed vertically. This mechanism is included in the Simon 27 series, a collection that makes a firm commitment to the total workplace solutions. It is more, all the plates of the series are compatible with any connector on the market.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Angled voice and data plate with dust cover, direct module for snap-fit connector, RJ45 category 5e UTP connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

PLATE TYPE

Angled

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.026

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

2871375

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046306

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

95

PACKAGING NET WEIGHT

0.26

UNITARY PACKAGING GROSS
WEIGHT

0.026

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

195