

Modular luminaire 726 60x60 under glare 4000K

REF. 72670033-684



BASIC INFORMATION

APPLICATION

General lighting, Office

ETIM CLASS

EC002892

TECHNICAL INFORMATION

IP RATING

IP20

COLOR TEMPERATURE (K)

4000 K

CRI

80

L70 (°C)

36.000 h a 25°C

LIGHT BEAM APERTURE ANGLE (°)

90°

LIGHTING EFFICIENCY (LM/W)

88,88 lm/W

LUMENS (LM)

3200 lm

OPTICS

Batwing 105°

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

POWER (W)

36 W

SERVICE LIFE

30.000 h

CHROMATICS CRI ICONS

CRI
80

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053274491

UNITARY PACKAGING HEIGHT

60

UNITARY PACKAGING WIDTH

740

UNITARY PACKAGING LENGTH

640

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

28416000

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

3

PRODUCT NET WEIGHT

2.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053274491

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

60

PACKAGING WIDTH

740

PACKAGING LENGTH

640

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

28416000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

3

PACKAGING NET WEIGHT

2.8

PACKAGING WEIGHT UNIT

KGM