

Mini jack connector female with trim plate white Simon K45

REF. K123B/9



BASIC INFORMATION

DESCRIPTION

Provides the maximum workplace solutions to its devices for audio and other systems with the analog mini jack connector 2.5 mm of Simon K45. This connector has a trim cover in white tone that, with its finishes simple, gives your room, the greater functionality, adapting to all types of spaces. With screw terminal connection, supports a maximum length of 30 meters and cabling wire section from 0.2 to 0.5 mm Made of thermoplastic materials, self-extinguishing and halogen-free, guarantees the security against possible to a fire, to prevent the flame spread and toxicity by smoke. Also, it has a temperature range of 5 ° C to 40 ° C and can reach temperatures that rocen the -25 and 50°C. The Simon K45 mini jack connector, ensures maximum workplace solutions for audio, elegance and innovation, minimising the space and maximizing the functionality.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Female mini jack connector, wire cable tie and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

FORMAT

Mini-Jack

RAL

9003

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

CONNECTOR TYPE

Mini-Jack

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF CONTACTS

3

NUMBER OF WIRES

3

NUMBER OF POSSIBLE ELEMENTS

1/2 element

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436064751

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436064751

PACKAGING VOLUME

0.012

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.019

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

40

PACKAGING NET WEIGHT

0.02

UNITARY PACKAGING GROSS
WEIGHT

0.02

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.02