

Monobloc kit for 1 element with 1 push-button switch and 1 USB charger 2.1A matt black Simon 270

REF. 27191610-098



BASIC INFORMATION

FINISH

Matt black

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC002949

MATERIAL

Plastic,Metal

PACKAGING CONTENTS

Mechanisms, frame+cover,
frame-holder and instruction
sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 45 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

Monoblock

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

USB CURRENT (A)

2,1 A

FORMAT

USB

USB VOLTAGE (V~)

127/230 V~

FREQUENCY

50 - 60 Hz

TYPE OF MECHANISM

Push | Insertion

VERSION

Monoblock

INDICATOR FUNCTION

No

MONOBLOCK

Yes

VOLTAGE (V~)

127/230 V~

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) | EN 50563:2011 | EN 50563:2011 A1:2013 | EN 60669-1:2018 | EN 62368-1:2014 | EN 62368-1:2014 A11:2017 | EN IEC 63000:2018 | ETSI EN 301489-34 V1.4.1 | ETSI EN 301489-34 V2.1.1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053283790

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.155

PRODUCT NET WEIGHT

0.155

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053283790

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

96

PACKAGING LENGTH

128

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

921600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.155

PACKAGING WEIGHT UNIT

KGM