

Floor trunking 2m and 130x18mm with 3 compartments

REF. TF11183/8



BASIC INFORMATION

DESCRIPTION

The DCS TF11183/8 floor trunking with anodized aluminum cover is ideal for the distribution of electrical and data cabling indoors, especially in demanding environments. With a 130x18 mm profile, it stands out for its IK07 protection rating, ensuring resistance to impacts and frequent use. It supports a maximum load of 55 kg/cm², making it suitable for offices, commercial spaces, and educational environments. Its installation is simple and fast, thanks to predefined fixing points, allowing easy access for maintenance through the removal of the cover with specific tools.

FINISH

Aluminium

MATERIAL

Aluminium

ETIM CLASS

EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION

07

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

55 Kg/cm²

MONOBLOCK

No

RAL

7035

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053229095

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0

PRODUCT NET WEIGHT

1.375

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436027923

UNITS CONTAINED PACKAGING

8

PACKAGING HEIGHT

90

PACKAGING WIDTH

145

PACKAGING LENGTH

2005

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

26165250

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

11

PACKAGING NET WEIGHT

11

PACKAGING WEIGHT UNIT

KGM