Downlight 800.23 White 24W 4000K DALI2

REF. **80023330-684**

BASIC INFORMATION

APPLICATION	PACKAGING CONTENTS	ETIM CLASS
General technical lighting	1 Units	EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

CRI
80

LUMENS/W
2400 lm/24W

IP RATING
IP54

ELECTRICAL CLASS
tipo 2

OPTICS
Closed

OPERATING TEMPERATURE RANGE (ºC)
-15ºC a 35ºC

L70 (ºC)
50.000 h a 25ºC

PHOTOBIOLOGICAL CLASSIFICATION
Categoría exento

POWER SUPPLY (V~)
220/240 V~

LIGHT BEAM APERTURE ANGLE (°)
24º

POWER (W)
24W

COLOR TEMPERATURE (K)
4000K

COLOR TYPE
NW

SERVICE LIFE
50.000 h

CONTROL
DALI2

LIGHTING EFFICIENCY (LM/W)
105 lm/W

COS Φ
0.95

LUMENS (LM)
2400 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT
115

INSTALLATION TYPE
Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Quick connector

REGULATIONS

WARRANTY
5 years 50.000 h

REGULATIONS
Dir. 2014/35/UE LVD |Dir. 2014/30/UE EMC|Dir. 2009/125/EC ErP (Reg. UE 2019/2020) |Dir. 2009/125/EC ErP (Reg. UE 2019/2015)|Dir. 2011/65/UE RoHS + post. mod|EN 60598-2-2:2012 |EN IEC 55015:2019 + A11:2020|EN 62493:2015 |EN 61547:2009|EN 62717:2017 + A2:2019 |EN IEC 61000-3-2:2019 + A1:2021|EN IEC 63000:2018 |EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053304525

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.09

PRODUCT NET WEIGHT
0.974

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053304525

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
145

PACKAGING WIDTH
250

PACKAGING LENGTH
215

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
7793750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.09

PACKAGING NET WEIGHT
0.974

PACKAGING WEIGHT UNIT
KGM