

Voice and data flat plate without dust cover for 1 element with 2 RJ45 connectors category 6 FTP white Simon K45

REF. KB096F/9



BASIC INFORMATION

DESCRIPTION

Voice and data flat plate with 1 element and 2 RJ45 category 6 FTP connectors in the collection Simon K45 with a soft finishes white in colour, it is the solution for the most electromagnetic compatibility, on the market. Its direct snap-fit RJ45 ports type is compatible with Keystone and accepted connection of cabling 22-24 AWG. Made of halogen-free, self-extinguishing thermoplastic prevents the flame spread and toxicity by smoke in case of fire. Designed for installation both recessed and surface-mounted, does not require tools screws, making it easier and minimizing the time of installation and maximizing its functionality. In case of combining it in vertical enclosures, requires the 90 ° positioner (ref.K66) to guide the plate and adapt it to the space in question. The flat base plate of voice and data K45, it is compatible with all types of connections on the market strengthening its functionality, innovation and quality assurance of the collection Simon K45.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Voice and data flat plate without dust cover, RJ45 category 6 FTP connectors

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

No

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

No

PLATE TYPE

Flat

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

Category 6 FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436047945

PACKAGING VOLUME

3.525

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

112

PACKAGING GROSS WEIGHT

0.45

UNITARY PACKAGING GROSS
WEIGHT

0.045

PACKAGING WIDTH

117

PACKAGING NET WEIGHT

0.45

PRODUCT NET WEIGHT

0.045

PACKAGING LENGTH

269

PACKAGING WEIGHT UNIT

KGM