

Flat voice and data plate with dust cover for 2 RJ45 Nexans® for 1 element white Simon 500 Cima

REF. 50018089-030



BASIC INFORMATION

DESCRIPTION

Simon 500 CIMA joins Nexans to give your space of work of the highest quality and functionality in data transmission thanks to the flat base plate with dust cover with 1 element and 2 RJ45 Nexans 1 component. With finishes in white, its design is prepared for installation in enclosures horizontal and vertical with direct snap-fit without the need of adapter. With an optimal bending radius for the transmission speed, the flat base plate 500 Cima, accepted cabling 22-26 AWG and their connectors have to be RJ45 Nexans. Composed of thermoplastic self-extinguishing halogen-free, it provides security to the space is a possible fire, reaching to reach temperatures of 5°C and 60 ° C. Also, the 500 Cima separating cabling electrical, voice, data and multimedia to delete interference and transmission errors. Simon 500 Cima is a guarantee of security, innovation and functionality.

FINISH

White

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

COMPATIBLE WITH CONNECTORS

Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

RJ45 CONNECTORS

Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

DUST PROTECTION

Yes

FORMAT

RJ45

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

1

PLATE TYPE

Flat

RAL

9003

RJ45 ADAPTOR MODULE

Included in voice and data plate

SNAP-FIT RJ45 PLATES

RJ45 Nexans® connectors

SNAP-FIT TYPE

RJ45 Nexans® connectors

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053097069

PACKAGING VOLUME
0.604

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
54

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.033

PACKAGING WIDTH
52

PACKAGING NET WEIGHT
0.33

PRODUCT NET WEIGHT
0.033

PACKAGING LENGTH
215

PACKAGING WEIGHT UNIT
KGM

