Neutral push-button switch 10A 250V~ with built-in light indicator and fast terminal connection system grey Simon 27 Play

REF. **27669-67**



BASIC INFORMATION

DESCRIPTION

It is a push-button switch 10A 250V~ neutral colour grey that includes a luminous light and quick terminal connection system. It is included in the Simon 27 Play series, a collection that provides of solutions for all kinds of environments, the piece is suitable for surface and flush mounting and has dimensions of 45x45 mm Manufactured in compliance with the regulations, it is composed of metal elements that include halogen-free thermoplastic material with halogen-free, while the trim is thermostable. For its resistance to extreme temperatures, the push-button switch is suitable for any space, although it is advisable that this piece to be installed in environments between 5 and 40ºC. It is compatible with the frames of the series Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua. In case of replacement of the indicator light, it is compatible with reference 2700802-064.

FINISH

Grey

MATERIAL

Thermoplastic

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000029

REMARKS

Can be combined with article 2700802-064 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

CONSUMPTION INDICATOR (MA)

0.55 mA

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

Yes

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Pivoting

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (ºC)

5 - 40 ºC

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 60669-1:2018|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252673

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
1229865

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.032

PRODUCT NET WEIGHT
0.032

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053071465

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
53

PACKAGING WIDTH
105

PACKAGING LENGTH
221

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1.23

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.315

PACKAGING NET WEIGHT
0.32

PACKAGING WEIGHT UNIT
KGM