729.60 60x60 Low Glare 3000K DALI2

REF. **72960333-683**

BASIC INFORMATION

DESCRIPTION

Modular LED luminaire 729, 595x595mm aluminium body with microprismatic diffuser for uniform glare-free lighting (UGR<19). 3000K CCT, CRI80, 3700lm, 108 lm/W. DALI-2 driver. Installation: suspended, recessed or surface mounted.

FINISH

White

APPLICATION

General lighting

MATERIAL

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
-20...+35

POWER SUPPLY (V~)
220/240 V~

CONTROL
DALI2

COLOR TYPE
WW

OPTICS
Diffused

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053357835

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
2

PRODUCT NET WEIGHT
1.75

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053357835

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
35

PACKAGING WIDTH
690

PACKAGING LENGTH
690

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
149730

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
2

PACKAGING NET WEIGHT
1.75

PACKAGING WEIGHT UNIT
KGM