
Simon iO master push-button panel, 2 functions for creating experiences bronze Simon 270

REF. **21021035-097**



BASIC INFORMATION

DESCRIPTION

Simon iO master push-button panel from the Simon 270 series, with two functions for creating lighting and control experiences. Push-button mechanism with indicator light and narrow rocker, compatible with Simon 270 minimalist-design frames. Made of thermoplastic, it measures 45 x 45 mm. It communicates via Wi-Fi for remote control and integration into the Simon iO ecosystem. Rated voltage 230 V~ at 50-60 Hz. Screw terminals for cable cross-sections from 1.5 to 2.5 mm, with 7 mm of stripped cable. Suitable for flush mounting in a universal back box, in a vertical or horizontal position. Protection rating IP20. Operating temperature range: 5 to 45 °C. Storage temperature range: -25 to 75 °C. Clean with a soft cloth lightly dampened with soapy water, avoiding abrasive or chlorine-based cleaners. Up to 9 available finish colours: 090 Glossy White; 190 Matte White; 091 Copper; 093 Aluminium; 094 Champagne; 095 Gold; 096 Titanium; 097 Bronze; 098 Matte Black.

FINISH
Bronze

MATERIAL
Thermoplastic

PACKAGING CONTENTS
Mechanism, rockers and instruction sheet

TYPE OF ROCKER
Slender

COMPATIBILITY
Simon 270 frames

ETIM CLASS
EC004265

REMARKS
Requires Simon Hub iO.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

IP RATING
IP20

POWER SUPPLY (V~)
127/230 V~

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL
3033

NUMBER OF POSSIBLE ELEMENTS
1 element

TYPE OF MECHANISM
Push

STORAGE TEMPERATURE RANGE (°C)
-25 - 75 °C

FREQUENCY
50 - 60 Hz

OPERATING TEMPERATURE RANGE (°C)
5 - 45 °C

VOLTAGE (V~)
127/230 V~

INDICATOR FUNCTION
Yes

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod.|Dir. 2014/53/UE RED|EN 50428:2005 |EN 50428:2005 A1:2007 |EN 50428:2005 A2:2009 |EN IEC 63000:2018 |ETSI EN 300328 V2.2.2

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053282311

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.077

PRODUCT NET WEIGHT
0.077

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053282311

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
80

PACKAGING WIDTH
55

PACKAGING LENGTH
55

PACKAGING MEASUREMENT UNIT
MMT


PACKAGING VOLUME
242000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.077

PACKAGING WEIGHT UNIT
KGM



Para información más detallada consultar la hoja de instrucciones
For more detailed information check the instruction sheet