

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e UTP aluminium Simon K45

REF. K95U/8



BASIC INFORMATION

DESCRIPTION

This plate of voice and data flat plate with dust cover for an element and a connector RJ46 category 5e UTP, in aluminium finish, it is part of the series Simon K45. The individual plate has a number of modules medium and is available with one or two connectors. The voice and data plate is manufactured from materials, with metal source self-extinguishing thermoplastic insulation. The material of manufacture is halogen-free, to guarantee the security in case of fire of the product, the dimensions of the plate of voice and data are 45x45 mm and a depth of 30 mm Requires cabling 22-26 AWG. To combine the plate with other vertical enclosures, it is necessary to incorporate the assembly the 90 ° positioner (ref. K66). Also, it can withstand a temperature range of -5 to + 60 degrees centigrade. It can be installed in surface-mounted or recessed. For its maintenance, it is sufficient to clean it with a soft, dry cloth cotton.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

PLATE TYPE

Flat

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e UTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.027

PRODUCT NET WEIGHT
0.027

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8426436046108

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
88

PACKAGING WIDTH
123

PACKAGING LENGTH
136

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
1472064

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.705

PACKAGING NET WEIGHT
0.27

PACKAGING WEIGHT UNIT
KGM