Plastic tray for square shallow floor box in concrete floor for 4 elements Simon 500 Cima

REF. **G201**



BASIC INFORMATION

DESCRIPTION

Esta cubeta de plástico de la serie Simon 500 Cima es el complemento ideal para una caja de suelo cuadrada para cuatro elementos. Está especialmente concebida para ser instalada de forma sencilla mediante empotramiento en suelos de pavimento de escasa profundidad. Lo único a tener en cuenta en su instalación es que el revestimiento del suelo debe colocarse hasta la entrada de la tapa protectora. La cubeta tiene unas medidas de 272 x 343 milímetros y 54 milímetros de profundidad, se compone de cuatro módulos y se presenta en un original color verde. Simon quiere adaptar sus productos a todo tipo de estancias y estilos decorativos. Por eso el diseño de sus artículos responde a las tendencias más innovadoras, como es el caso de esta cubeta verde. Los materiales de la cubeta son de la mejor calidad, lo que asegura su óptimo funcionamiento incluso bajo elevadas temperaturas. El material termoplástico libre de halógenos con el que está fabricada, consigue que en caso de incendio no se propaguen las llamas y además reduce la toxicidad del humo, lo que confiere mucha seguridad al conjunto final.

FINISH

Green

MATERIAL

Plastic

PACKAGING CONTENTS

Tray and protective cover with installation manual

ETIM CLASS

EC000114

REMARKS

The floor lining must be installed up to the protective cover inlet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

4, 6 and 8 elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (ºC)

+90 ºC

HEAT RESISTANCE (ºC)

+125ºC (according rule IEC 60695-10-2)

IK CLASSIFICATION

08

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

IP RATING

IP4X

KIT AVAILABILITY

No

TEMPERATURE RANGE DURING INSTALLATION (ºC)

-5 to 60 ºC

NUMBER OF MODULES

4 modules

RECESS DIMENSION (MM)

272 x 343 mm

NUMBER OF SIDE ENTRANCES

8

VERSION

4 elements

INSTALLATION AND MAINTENANCE

NUMBER OF CHANNEL ENTRIES

2

EXTINGUISHING (ºC)

+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using screws

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Specially designed for installation in concrete floors

SCREWS REQUIRED FOR SLAB FIXING

Minimum 2 (1 per side, diagonally). It is recommended to fix the bowl with 6 screws for complete fixation.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053090572

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.95

PRODUCT NET WEIGHT
0.95

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053090572

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
55

PACKAGING WIDTH
285

PACKAGING LENGTH
355

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
5.565

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.95

PACKAGING WEIGHT UNIT
KGM