Fuse-holder base for half element for cylindrical fuses 16A 250V~ size 5x20 mm ivory Simon 27 Play

REF. **27000-31**



BASIC INFORMATION

DESCRIPTION

This product is ideal for arrange cylindrical fuses and so spaces more cleaner. It is a socket for medium element fuse holders for current of up to 16 A of current and 250 volts. It is part of the Simon 27 Play series. This fuse holder socket has a size of 5 x 20 millimetres and comes in a beautiful and sophisticated ivory colour finish, which gives much elegance to the product as well as place in which it is installed. The product is suitable both for surface-mounted and recessed installation by means of recessed and its terminal system is very simple and is made by screw. The operating mode is by means of a cylindrical fuse. It is a product of great resistance capable of working normally low temperatures very high or low, and to resist well possible damage external as knocks or scratches. This is possible thanks to the materials of manufacture of the socket which is made of metal components with halogen-free insulation. Meanwhile, the trim is made of thermoplastic.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Fuse holder

ETIM CLASS

EC000011

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

NUMBER OF POSSIBLE ELEMENTS
Half element

INDICATOR FUNCTION
No

CURRENT (A)
16 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

MODE OF OPERATION
Cylindrical fuse

POWER SUPPLY (V~)
250 V~

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American, Small spaces and Centralisations

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 60127-6:2014|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
23

UNITARY PACKAGING WIDTH
37.5

UNITARY PACKAGING LENGTH
46

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.04

UNITARY PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING GROSS WEIGHT
0.036

PRODUCT NET WEIGHT
0.031

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053010174

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
52

PACKAGING WIDTH
102

PACKAGING LENGTH
222

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1.177

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.71

PACKAGING NET WEIGHT
0.62

PACKAGING WEIGHT UNIT
KGM