

## Module for 1 Keystone II RJ45 AMP®, Brand Rex® or Simon® in angled voice and data plates

REF. MD67



### BASIC INFORMATION

#### DESCRIPTION

This product consists of a module for 1 Keystone II RJ45 from AMP®, Brand Rex® or Simon® in angled voice and data belonging to the Simon 500 Cima series. The module is exclusively designed for plates of this range of type inclined, as the angled voice and data plates for Simon are included with the module. Its dimensions are 32 x 20 millimetres and 10 millimetres of depth, and its installation is very simple. The product is made of thermoplastic insulation. These components are of the highest quality, as well as all the used by Simon. Thanks to the product has a resistance and hardness extra that extends considerably its service life and allows you to operate even low temperatures ranging from -5 and 60 degrees centigrade. Added to all this is the capacity of the module extinguish the spread in case of fire management and reduces the toxicity in the flue gas in case of producing. Which contributes without a doubt to increase in a considerable the security of the end product.

#### COMPATIBILITY

Simon 500 Cima and Simon K45 angled voice and data plates

#### PACKAGING CONTENTS

MD Module for 1 RJ45

#### ETIM CLASS

EC002948

#### REMARKS

The MD Module can only be combined with angled voice and data plates (flat voice and data plates do not include the MD Module on the plate itself).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### AVAILABLE IN

MD Module for 1 RJ45

### COMPATIBLE WITH CONNECTORS

Simon®, AMP netconnect® Series Standard 110, SL110, SL Tool less, Brand-Rex®, Panduit® Series Netkey, Rit® and manufacturers of RJ45 with Keystone II snap-fit system.

### RJ45 CONNECTORS

Not included in the MD Module

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

### FORMAT

RJ45

### KIT AVAILABILITY

Yes

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

### SNAP-FIT RJ45 PLATES

RJ45 AMP®, Brand Rex® or Simon® connectors

### SNAP-FIT TYPE

RJ45 AMP®, Brand Rex® or Simon® connectors

## INSTALLATION AND MAINTENANCE

### INSTALLATION DIRECTION

Vertical, corresponding with the MD Module fastening slots

### INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

## REGULATIONS

### REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018\*1

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT 0	PRODUCT NET WEIGHT 0.003	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING VOLUME 455000
UNITARY PACKAGING LENGTH 0	PACKAGING EAN 8426436025394	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING VOLUME 0.3	UNITS CONTAINED PACKAGING 50	PACKAGING GROSS WEIGHT 0.15
UNITARY PACKAGING VOLUME UNIT MMQ	PACKAGING HEIGHT 65	PACKAGING NET WEIGHT 0.15
UNITARY PACKAGING GROSS WEIGHT 0.003	PACKAGING WIDTH 70	PACKAGING WEIGHT UNIT KGM
	PACKAGING LENGTH 100	