German socket outlet monoblock IP55 16A 250V~ with safety device and fast terminal connection grey Simon 44 Aqua

REF. **4490432-035**



BASIC INFORMATION

DESCRIPTION

Schuko monoblock socket-outlet with, IP55, 16A current and a voltage of 250V. It, in addition, with safety device, it belongs to the series Simon 44 Aqua and is finished in grey colour. Its clamping is fast type and its operation is by insertion. With 1 element and supports a section of wire 2.5 mm with a stripped 15 mm and can be position, place in rooms with a temperature located between 5 and 40ºC, approximately, although it is able to withstand extreme temperatures of -25 to 50ºC, plus or minus. It is made of metal components with halogen-free insulation and thermoplastic trim, materials that are very easy to clean because it will only need to use a soft and dry cloth and never use abrasive cloths or cleaners containing chlorine. Its dimensions are 84x75 mm and has a depth of 57,5 mm

FINISH

Grey

COMPATIBILITY

Simon 27 mechanisms

PACKAGING CONTENTS

Socket outlet, base and frame with cover

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
2,5 mm

NUMBER OF POSSIBLE ELEMENTS
1 element

FORMAT
Schuko

IK CLASSIFICATION
07

INDICATOR FUNCTION
No

CURRENT (A)
16 A

IP RATING
IP55

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

MONOBLOCK
Yes

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

RAL
7035

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
15

INSTALLATION DIRECTION
Vertical

INSTALLATION TYPE
Suitable for surface mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018*1 | IEC 60884-1 Ed. 3.2*2 | UNE 20315-1-1:2017*2 | UNE 20315-1-2:2017*2 | EN IEC 60670-1:2021 + A11:2021*3 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.168

PRODUCT NET WEIGHT
0.168

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053069905

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
86

PACKAGING WIDTH
155

PACKAGING LENGTH
306

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4.079

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
1.75

PACKAGING NET WEIGHT
1.68

PACKAGING WEIGHT UNIT
KGM