

Flush-mount trim cover for adjustable floor box or service cover 4 elements grey Simon 500 Cima

REF. 52053102-035



BASIC INFORMATION

DESCRIPTION

Specially designed to be installed in raised floor, the adjustable Floor box for four elements in grey colour of the Simon 500 Cima series is one of the most demanded products to be installed in all types of public and private buildings, thanks to their quality and low price. This is an element of 171 x 187 x 92 mm with an innovative design that matches all types decorations. It also stands out the strength of its structure against knocks, impacts thanks to the metal components with self-extinguishing and halogen-free thermoplastic insulation., a material that guarantees no flame propagation in case of fire and the low toxicity in case of smoke. Also, once the product has been configured and installed, as an option, it may be combined with the flush-mount trim cover (ref.52053102-035) in cases where you do not install the same floor covering.

FINISH

Grey

PACKAGING CONTENTS

Trim cover

MATERIAL

Plastic

ETIM CLASS

EC002417

REMARKS

Optional element. To combine with the floor box if not installing the same floor finish.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IK CLASSIFICATION

08

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

2, 4, 6, 8 and 12 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

4 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP4X

RAL

7011

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

KIT AVAILABILITY

No

VERSION

4 elements

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

INSTALLATION DIRECTION

Horizontal, Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053101506

PACKAGING VOLUME
2.116

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
75

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.077

PACKAGING WIDTH
165

PACKAGING NET WEIGHT
0.77

PRODUCT NET WEIGHT
0.077

PACKAGING LENGTH
170

PACKAGING WEIGHT UNIT
KGM

