

S-Video connector female with trim plate aluminium Simon K45

REF. K103B/8



BASIC INFORMATION

DESCRIPTION

Give the highest quality at the signal to connect your computer to the screen, with the S-Video female connector of the collection Simon K45 including a trim cover finished in Aluminium, the S-Video connector, K45, not only will ensure the best quality of video with image enhanced but sophistication of finishes that adapt perfectly to the set of the space. Composed of materials with thermoplastic isolated free of halogens, it inhibits the flame spread in case of fire and smoke. The connector reaches temperatures that vary the -25 and 50°C. With screw terminal connection, it is suitable for its assembly in surface-mounted or flush-mounted, allowing a maximum length of 30 meters and cabling a cable section cross-section of 0.2 to 0.5 mm With a resolution of video standard and speed of 400 Megabit / second, the Simon K45 S-Video connector, female, is the hallmark of security and functionality in a single space.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

Female S-Video connector, wire cable tie and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

CONNECTOR TYPE

S-Video

NUMBER OF CONTACTS

4

NUMBER OF POSSIBLE ELEMENTS

1/2 element

FORMAT

S-Video

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

NUMBER OF WIRES

5

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436064683

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436064683

PACKAGING VOLUME

0.012

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.025

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

42

PACKAGING NET WEIGHT

0.025

UNITARY PACKAGING GROSS
WEIGHT

0.025

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.025