

## Downlight 725.22 Flush mount NW General IP44 White

REF. 72522930-984



### BASIC INFORMATION

#### DESCRIPTION

Protected against the entry of external agents such as water or dust, thanks to the system IP44 included in the Downlight 725.22 Advance of Simon, makes it the best option to bring to the space of the maximum guarantee of security and lighting. Energy savings of its LED technology category B, is linked to its performance of 2300 lm for NW, and total luminaire consumption of 24 W and compatible with power supplies 100-240 Volts and 50-60 Hertz rate. It has a colour temperature of 3900 K obtaining a white tone neutral NW, and provides to each space a ambience visually comfortable thanks to its optics, also, for General photometric distribution. With control system, switching on ON-OFF, it has a service life of 30,000 hours at 25 ° C, which is not affected the quantity (QTY.) of times are power on or off luminaire. Also, it is designed for flush installation that, together with its finishes in a high colour White, guarantee total integration of the set in any space.

#### APPLICATION

General lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY (HZ)

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS (LM)

2300 lm

### IP RATING

IP44

### ELECTRICAL CLASS

Type 1

### LUMENS/W

2300 lm/24W

### OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

### INTEGRATED POWER SUPPLY

Yes

### OPTICS

General

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

30,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

3900 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

24 W

### CONTROL

On/Off

### COLOR TYPE

NW

### SERVICE LIFE

30.000 h


### CRI

80

### LIGHTING EFFICIENCY (LM/W)

96 lm/W

### CHROMATICS CRI ICONS



## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface

### INSTALLATION TYPE

Flush mount

### MINIMUM INSTALLATION HEIGHT

107

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.442

### PRODUCT NET WEIGHT

1.442

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053116777

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

70

### PACKAGING WIDTH

245

### PACKAGING LENGTH

245

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

0.042

### PACKAGING VOLUME UNIT

HLT

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.442

### PACKAGING WEIGHT UNIT

KGM