

Projector 889 150W 5500K

REF. 88934038-885



BASIC INFORMATION

DESCRIPTION

Exterior LED projector for showcase and facade lighting, robust, adjustable and designed for high performance in commercial applications. Available in different power ratings, the 889 exterior projector allows you to select the appropriate model according to the mounting height, the surface to be illuminated and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 5500K. Power: 150W. Lumens: 13500lm. Efficiency: 90lm/w. IP protection rating: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 331 mm x 278 mm x 47 mm.

APPLICATION

Wall lighting, Industrial
lighting, Commercial areas

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

05

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+50

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

90 lm/W

LUMENS (LM)

13500 lm

OPTICS

Symmetric

POWER (W)

150 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440452

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.607

PRODUCT NET WEIGHT

1.53

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440452

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

300

PACKAGING WIDTH

230

PACKAGING LENGTH

355

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

24495000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

6.428

PACKAGING NET WEIGHT

1.53

PACKAGING WEIGHT UNIT

KGM