

Complete set with 6 schuko socket outlets black S400 Top

REF. 42606000-138



BASIC INFORMATION

DESCRIPTION

Desk top complete kit with 6 socket-outlet Schuko, black in colour and of the Simon series 400. Its dimensions are 295 x 120 x 80 mm and its type manual elevation and has a current of 16 A and works with a voltage of 250V. It can withstand heat of over 70 and its trim cover is made of painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free, which guarantees the no-propagation of the flame in case of fire and low toxicity in case of smoke. It is a kit suitable to be flush mounted in furniture and is fixed through clamps that are pages and to clean this kit only have to clean with a soft, dry cloth and do not use cloths or abrasive cleaners containing chlorine in its formulation, as it could be damaged and does not operate correctly.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9005

NUMBER OF SOCKETS

6 sockets for standard current circuit

VERSION

6 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053196205

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.15

PRODUCT NET WEIGHT

1.15

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053196205

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

330

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.15

PACKAGING WEIGHT UNIT

KGM