

Beacon GL 85 600 BT Mesh 9W 3000K with detector 5m 160° HF+LUX IP44

REF. 89317602-893



BASIC INFORMATION

DESCRIPTION

Beacon with HF detector and Bluetooth connectivity. The power is 9 W, the luminous flux is 655 lm, and the color temperature is 3000 K. The maximum installation height is 4m, and the installation is on the floor. The detection range is 5m, and the detection angle is 160 °. The brightness regulation range is 2 - 2000 lux, and the timing range is 5 s - 60 min. The luminaire configuration is done through a Bluetooth application. Possibility of interconnection between luminaires via Bluetooth mesh. The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C. Protection rating IP 44 and IK 03, and dimensions: 136 x 146 x 600 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Anthracite

ETIM CLASS

EC000301

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053400272

UNITARY PACKAGING GROSS WEIGHT

3.045

PACKAGING LENGTH

530

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

2.04

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053400272

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

3.045

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

185

PACKAGING NET WEIGHT

2.04

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

185

PACKAGING WEIGHT UNIT

KGM