Plastic bucket for adjustable floor box with 2 double elements for pavement floor installation Simon Cima

REF. **G22**



BASIC INFORMATION

FINISH
Grey

MATERIAL
Thermoplastic

COMPATIBILITY
With adjustable floor boxes of 2 double elements for pavement and inspection covers of 2 double elements Simon Series S.

ETIM CLASS
EC000114

TECHNICAL INFORMATION

HEAT RESISTANCE (ºC)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

KIT AVAILABILITY

No

RECESS DIMENSION (MM)

220 x 172.2 mm

INSTALLATION AND MAINTENANCE

NUMBER OF CHANNEL ENTRIES

2

EXTINGUISHING (ºC)

+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

SCREWS REQUIRED FOR SLAB FIXING

Minimum 2 (1 on each side, diagonal). It is recommended to secure the mounting box with 4 screws for maximum secure fixation

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436013926

UNITARY PACKAGING HEIGHT
75

UNITARY PACKAGING WIDTH
186

UNITARY PACKAGING LENGTH
226

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
3.153

UNITARY PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING GROSS WEIGHT
0.755

PRODUCT NET WEIGHT
0.755

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436013926

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
75

PACKAGING WIDTH
186

PACKAGING LENGTH
226

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3.153

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.755

PACKAGING NET WEIGHT
0.755

PACKAGING WEIGHT UNIT
KGM