

Simon XENON Wall Charging Point with T2 Socket Three-phase 22 kW + Automatic and Differential

REF. 0660121-100



BASIC INFORMATION

DESCRIPTION

Charging point SIMON XENON BUSINESS Series, wall-mounted. Type 2 socket with connector locking to prevent its removal. Maximum power per socket of 22 kW (three-phase 400 V, 50 Hz) configurable to lower powers by means of software. Mode 3 charging according to EN 61851-1. Master-slave management system between charging points with possibility of fixed power management. Compatible with SPL SIMON accessory for dynamic balancing. Digital LED strip indicating status by color code on the front. LCD display screen for user interaction prepared for outdoor and indoor. RFID card reader ISO 14443A/Mifare – 13.56 MHz. Two RFID cards are included for the use of the charging point. Meter included per socket with MID certificate. Communications RS-485, Ethernet, 4G (Optional). OCPP 1.6 JSON and Modbus TCP/IP protocol. PC + ABS V0 IK10 and IP54 enclosure suitable for indoor or outdoor installation, of 351 x 343 x 148 mm. Residual current detection per socket: 6 mA DC. Electrical protection included per socket: differential (RCD) Class A sensitivity 30 mA and circuit breaker (MCB) Curve C. Standard finish SIMON.

APPLICATION

Commercial
areas,Hotel,Office,Parking

OPERATING ENVIRONMENT

Commercial
areas,Hotel,Office,Parking

ETIM CLASS

EC002883

REMARKS

To carry out a dynamic power balancing with the installation, the SPL network analyzer accessory must be acquired. Vertical mounting totems are available.

TECHNICAL INFORMATION

4G COMMUNICATION MODEM

With accesorie

FREQUENCY

50 Hz

IP RATING

IP54

CONNECTOR TYPE

Type 2 Socket

IK CLASSIFICATION

10

TYPE OF LINE

Three-phase

ELECTRICITY METER

Yes

CURRENT (A)

32 A

NUMBER OF OUTLETS

1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053349687

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053349687

PACKAGING VOLUME

60735500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

225

PACKAGING GROSS WEIGHT

7

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

500

PACKAGING NET WEIGHT

6.5

UNITARY PACKAGING GROSS
WEIGHT

7

PACKAGING LENGTH

435

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

6.5