

Voice and data flat plate with dust cover for 1 element and 1 RJ45 connector category 5e FTP white Simon K45

REF. K95F/9



BASIC INFORMATION

DESCRIPTION

Voice and data flat plate with dust cover with 1 element for 1 RJ45 connector of category 5e FTP white in colour, measures 45x45 mm and 42,9 mm depth. The product is made up of metal parts with halogen-free thermoplastic of character self-extinguishing and halogen-free. This type of material is resistant to high temperatures and prevents the fire is spread of a fire. The plate, in addition, it is in compliance with the regulations and is suitable for both surface and flush mounting. It is compatible with any connector of the market and allows its integration in vertical enclosures the type of columns, mini columns, Teleblock. This article is available in the Simon 27 series, a collection that includes a wide range of panels and connectors to facilitate the workplace solutions in the day to day life in all kinds of environments.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

NUMBER OF MODULES

Half

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

DUST SHUTTER

Yes

PLATE TYPE

Flat

AVAILABLE IN

Plate with 1 and 2 RJ45 connectors

FORMAT

RJ45

RAL

9003

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with the voice and data plate

CONNECTOR CHARACTERISTICS

Category 5e FTP

KIT AVAILABILITY

No

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.031

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2115750

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436032002

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.65

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

65

PACKAGING NET WEIGHT

0.31

UNITARY PACKAGING GROSS WEIGHT

0.031

PACKAGING WIDTH

155

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

210