

Flush-mount trim cover circular shallow floor box for 6 elements grey Simon 500 Cima

REF. 52053203-035



BASIC INFORMATION

DESCRIPTION

Component of the box Circular model 52053203-035 belonging to the range of products professionals Simon 500 Cima, with capacity for easy combination with other elements of The Simon 500 Cima range is an element, designed to facilitate the installation In flush mounted in concrete floor and raised floor. Trim cover for Flush-mounted floor box for shallow circular, version for 6 Elements, manufactured in plastic material and with finishes in tonality and Grey colour. Integrated components of character halogen-free thermoplastic That guarantees no flame propagation in case of fire and the low Toxicity in case of smoke. Component is ideal for All types of installations and systems professionals assembly, with dimensions of Ø 244 mm x 5 mm, ideal for endorse an element essential to have in Concrete floor and raised floor.

FINISH

Grey

PACKAGING CONTENTS

Trim cover

MATERIAL

Plastic

ETIM CLASS

EC002417

REMARKS

Optional element. To combine with the floor box if not installing the same floor finish.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IK CLASSIFICATION

08

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

4, 6 and 8 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

6 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP4X

RAL

7011

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

KIT AVAILABILITY

No

VERSION

6 elements

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

INSTALLATION TYPE

In raised or concrete floor with shallow floor boxes

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

INSTALLATION DIRECTION

Circular, in line with the installation of the floor box

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

84210531016810

PRODUCT NET WEIGHT

0.145

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

453250

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

84210531016810

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

5

PACKAGING NET WEIGHT

0.145

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

370

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.145

PACKAGING LENGTH

245