

Adjustable depth drawer for 6 S modules to be installed in a false floor color graphite Simon CIMA

REF. SF610/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With Simon Series S mechanisms and Simon 25 / Simon K45 (via adapter)

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

16

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1800kg

RAL

7021

RECESS DIMENSION (MM)

210 x 300 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436052628

PRODUCT NET WEIGHT

2.248

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

7483280

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436052628

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.27

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

98

PACKAGING NET WEIGHT

2.248

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

230

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

2.248

PACKAGING LENGTH

332