

## DALI downlight white 735.31 WW Extensive

REF. 73531330-783



### BASIC INFORMATION

#### APPLICATION

Accent lighting, General lighting

#### PACKAGING CONTENTS

1 unit

## TECHNICAL INFORMATION

### IP RATING

IP20

### DRIVER INCLUDED

Yes

### LUMENS/W

3200 lm/33W

### OPERATING TEMPERATURE RANGE (°C)

Max. temp.: 35°C

### L70 (°C)

50,000 h

### OPTICS

Extensive

### COLOR TEMPERATURE (K)

3000 K

### L90 (°C)

50,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### CONTROL

DALI

### COLOR TYPE

WW

### POWER (W)

33 W

### CRI

80

### LIGHTING EFFICIENCY (LM/W)

97 lm/W

### SERVICE LIFE

50.000 h

### LUMENS (LM)

3200 lm

## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface-mounted

### INSTALLATION TYPE

Flush-mounted

## REGULATIONS

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053235669

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.5

### PRODUCT NET WEIGHT

1.2

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053235669

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

135

### PACKAGING WIDTH

285

### PACKAGING LENGTH

255

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

9811125

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

1.5

### PACKAGING NET WEIGHT

1.2

### PACKAGING WEIGHT UNIT

KGM