

Downlight 719 5W 3000K

REF. 71920030-983



BASIC INFORMATION

DESCRIPTION

Neutral and subtle integration downlight. It allows for general lighting in all types of spaces. Installation type: Flush-mounted. Optics: Microprismatic. Color temperature: 3000K. Power: 5W. Lumens: 439lm. Efficiency: 87.8lm/w. IP protection degree: IP20. Power supply: 220-240 V. 50/60 Hz. Dimensions: 90 mm x 35 mm.

APPLICATION

Ambient
lighting, Domestic, Residential

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

LUMENS (LM)

439 lm

IP RATING

IP20

CONTROL

On/Off

OPTICS

General

OPERATING TEMPERATURE RANGE (°C)

-25...+50

LIGHTING EFFICIENCY (LM/W)

88 lm/W

POWER (W)

5 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Recessed

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053440162

PACKAGING VOLUME
1714750

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
5

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
95

PACKAGING GROSS WEIGHT
0.3

UNITARY PACKAGING GROSS
WEIGHT
0.06

PACKAGING WIDTH
95

PACKAGING NET WEIGHT
0.25

PRODUCT NET WEIGHT
0.05

PACKAGING LENGTH
190

PACKAGING WEIGHT UNIT
KGM