

Monobloc kit for 1 element with 1 push-button switch and 1 USB charger 2.1A gold Simon 270

REF. 27191610-095



BASIC INFORMATION

FINISH

Gold

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC002949

MATERIAL

Plastic,Metal

PACKAGING CONTENTS

Mechanisms, frame+cover,
frame-holder and instruction
sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 AX

OPERATING TEMPERATURE RANGE (°C)

0...+35

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

POWER SUPPLY (V~)

127/230 V~

NUMBER OF POSSIBLE ELEMENTS

Monoblock

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

USB

TYPE OF MECHANISM

Push | Insertion

USB CURRENT (A)

2,1 A

FREQUENCY

50 - 60 Hz

USB VOLTAGE (V~)

127/230 V~

INDICATOR FUNCTION

No

MONOBLOCK

Yes

NOMINAL VOLTAGE (V~)

127/230 V~

VERSION

Monoblock

INSTALLATION AND MAINTENANCE

CLAW

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) | EN 50563:2011 | EN 50563:2011 A1:2013 | EN 60669-1:2018 | EN 62368-1:2014 | EN 62368-1:2014 A11:2017 | EN IEC 63000:2018 | ETSI EN 301489-34 V1.4.1 | ETSI EN 301489-34 V2.1.1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053283769

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053283769

PACKAGING VOLUME

921600

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

75

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

96

PACKAGING NET WEIGHT

0.1

UNITARY PACKAGING GROSS WEIGHT

0.1

PACKAGING LENGTH

128

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.1