

Trim plate for 1 quick connection connector with 3 poles male or female for 1 element white Simon K45

REF. K18/9



BASIC INFORMATION

DESCRIPTION

Trim plate of the series Simon K45 available in white colour and that is used for 1 connector is not included (to be purchased the plate) of connection 3-pole male or female quick of 1 element. This plate is made (according to the regulation UNE -s 60670-1: 2006) with halogen-free thermoplastic material, a material very safe that guarantees no flame spread in case of fire and low level poison in case of fire and smoke. The trim plate Simon K45 is perfect to be installed both in surface-mounted and recessed, in rooms with a temperature located between the -5 and the most of 60 ° C It measures 45 x 45 x 8.5 mm and its cleaning is very simple: You just need a soft, dry cloth and do not use any type of abrasive cleaner containing chlorine, as the plate could get damaged and not function as it should.

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Plate for one 3-pole quick connection connector

ETIM CLASS

EC000011

REMARKS

Connector not included (to be purchased separately). If using another quick connect brand, the plate is compatible with the leading manufacturers (Wieland®, Wago®, etc). To fix the connector to the plate correctly, the clips must be between 1.5 and 2 mm thick.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

AVAILABLE IN

Versions for 1 and 2 quick-connection connectors with 3 male or female poles

IP RATING

IP20

NUMBER OF MODULES

Half

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

KIT AVAILABILITY

No

RAL

9003

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

FORMAT

GST18

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE PLATE

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60535:2009 A1:2013

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.009

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

911400

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436036697

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.18

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.18

UNITARY PACKAGING GROSS

WEIGHT

0.009

PACKAGING WIDTH

93

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

140