

MD-24 PIR+LUX surface On/Off white IP54

REF. 89208136-130



BASIC INFORMATION

DESCRIPTION

Surface-mounted PIR motion and light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360°. The tangential detection range is 24 m and the radial detection range is 5.5 m.

The light regulation range is 2 - 1000 lux and the timing range is 5 s - 60 min. The configuration of the detector is carried out through potentiometers and remote control.

It features a TEACH operating mode. Possibility of interconnection between master/master sensors up to 10 detectors. The control output is On/Off and the maximum switchable power is 2000 W (500 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50°C.

White finish, IP 54 protection rating, and dimensions: Ø 129 x 70 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

CONTROL

On/Off

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342138

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.332

PRODUCT NET WEIGHT

0.257

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342138

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

90

PACKAGING LENGTH

135

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1579500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.332

PACKAGING NET WEIGHT

0.257

PACKAGING WEIGHT UNIT

KGM