

2-way switch for card with 1 micro switch and light indicator 250V~ graphite Simon 75

REF. 75526-38



BASIC INFORMATION

DESCRIPTION

The 2-way switch for card switch with a microswitch part of the collection of mechanisms of the Simon 75 series, with its finished in graphite, it incorporates an indicator light. Composed by an element in its individual version adapts to its function perfectly. With reference 75526-38. With an intensity of 6 A and a voltage of 250V~ The installation can be perform either in surface-mounted and in any universal recessed box. Its operation is per card and the rocker operation is fast operation. The cross-cable section is 0.5mm. It is made by several metal components with a halogen-free insulation. It incorporates a trim made of thermoplastic.

FINISH

Graphite

COMPATIBILITY

Simon 75 frames

PACKAGING CONTENTS

Mechanism and cover

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INDICATOR FUNCTION Yes	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) 0,5 mm	CURRENT (A) 10 (1,5 ind.) A	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
CONSUMPTION INDICATOR (MA) 1 mA	IP RATING IP20	POWER SUPPLY (V~) 250 V~
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
FREQUENCY 50 Hz	TYPE OF MECHANISM Card	VERSION Single

INSTALLATION AND MAINTENANCE

CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Faston
INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for surface and flush mounting	

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + + EN 61058:2002 + EN 61058:2002 A2:2008 + EN 61058-2-1:2011

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.08

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

3017190

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053044285

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

1517738

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0.4

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

82

PACKAGING NET WEIGHT

0.4

UNITARY PACKAGING GROSS
WEIGHT

0.08

PACKAGING WIDTH

83

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

223