

PD-24x24 PIR+LUX BT Mesh surface IP white IP20

REF. 89212536-230



BASIC INFORMATION

DESCRIPTION

PIR surface presence and luminosity detector. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 24 x 24 m and the radial detection range is 9 x 9 m.

The luminosity regulation range is 2 - 2000 lux. The detector configuration is done via Bluetooth and IP application.

It has a TEACH operating mode. Possibility of interconnection between sensors via Bluetooth. The control protocol is IP.

The power supply voltage is PoE (24 - 55 V). The operating temperature of the detector is: 0 - 40 °C.

White finish, IP protection grade 20, and dimensions: 123 x 123 x 64 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

Standard PoE (IEEE 802.3af)

CONTROL

IP

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342442

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.38

PRODUCT NET WEIGHT

0.246

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342442

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.38

PACKAGING NET WEIGHT

0.246

PACKAGING WEIGHT UNIT

KGM