

On-desk set with 5 German socket outlets aluminium Simon 400

REF. 42505000-133



BASIC INFORMATION

DESCRIPTION

For the environment suits your needs, Simon 400 offers the kit full of 5 socket-outlets ground, ideal to optimise the space and to win in functionality in working areas. With aluminium finishes and a design of simple lines, the kit is integrated into all types of decorative spaces and environments. Its flush installation does not require additional tools, thanks to the quick connection Wieland, reducing the time of assembly and increasing the performance of the product, it also has a compact design of a dimension of 250 x 120 mm and a depth of 80 mm, making the installation and adapting the set in the space. Compatible with a voltage of power of 250 Volts, and 16 Ampere current, its resistance of insulation is > 5 M Ω at 500 V, with a dielectric strength of 2000 V at 50H per minute. This kit is the perfect solution to obtain a configuration versatile in a simple design and compact thanks to Simon 400.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

NOMINAL VOLTAGE (V~)

250 V~

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

CURRENT (A)

16 A

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

IP RATING

IP30

RAL

9006

FORMAT

Schuko

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NUMBER OF SOCKETS

5 sockets for standard current circuit

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

VERSION

5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195932

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053195932

PACKAGING VOLUME

3675000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

300

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

125

PACKAGING NET WEIGHT

0.85

UNITARY PACKAGING GROSS WEIGHT

0.85

PACKAGING LENGTH

98

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.85