

Recessed movement and brightness detector 16 m white

REF. 89102114-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted motion and light detector. The recommended installation height is 2.5 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 16 m and the radial detection range is 8 m.

The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 20 min. The detector configuration is performed via potentiometers.

The control output is potential-free and the maximum switching current is 5 A (50 - 240 VAC) and up to 64 W LED.

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, protection grade IP 20 and dimensions: Ø 83 x 82 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9010

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053356463

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.237

PRODUCT NET WEIGHT

0.186

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053356463

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

125

PACKAGING LENGTH

164

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1845000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.237

PACKAGING NET WEIGHT

0.186

PACKAGING WEIGHT UNIT

KGM