

Extension 1.5 metres for square aluminium column with 2 sides Simon K45

REF. ALK22P15/8



BASIC INFORMATION

DESCRIPTION

Extension of 1.5 metres for pole of 2 sides oval aluminium of the series Simon K45. This pole has dimensions of 1500 x 80 x 80 mm and to ensure its robustness, just you can combine one extension per pole. Made in anodised aluminium, follow the regulation UNE-EN 50.085-2-4: 2006 and extension is a perfect for use in rooms with a temperature between -25° and the most of 120 ° C, so it is ideal for use in any type of climatology. If you want to clean this extension and make it in perfect condition, just use a soft and dry cloth, forgetting to use any cloth and / or abrasive cleaner containing any quantity (QTY.) chlorine. The columns of the series Simon K45 fixing to the slab by applying pressure, and it is not necessary to screw them together to the floor, that is, without the need for screwing to concrete floor or the slab.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

VERSION

2-sided, (Square)

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using connecting pins

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050594

PRODUCT NET WEIGHT

3.4

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

15.917

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436050594

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

3.4

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

88

PACKAGING NET WEIGHT

3.4

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

119

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

3.4

PACKAGING LENGTH

1520