

Customisable set with 1 schuko socket outlet and 4 empty elements black S400 Top

REF. 42501000-138



BASIC INFORMATION

DESCRIPTION

Take the most of its devices connection kit desk top customizable of the collection Simon 400 Top. With 1 Schuko socket-outlet empty and 4 elements, you can choose the one that best adapt to the needs of the space. Finishes in black and with a compact design, this kit is integrated into all types of spaces, adding a current and minimalist style. Connected to figure Wieland gst 18i power, its voltage is 250 Volts, and 16 Ampere current, with a dielectric strength of 2000 V at 50H / minute and insulation resistance > 5 M Ω at 500 V. Manual elevation and designed for flush installation in furniture, its assembly does not require additional tools, guaranteeing a quick and easy installation from the top of the table, or desktop. To optimise the space getting functionality is possible thanks to this kit customizable of Simon 400 Top.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

4

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

NOMINAL VOLTAGE (V~)

250 V~

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9005

NUMBER OF REAR ENTRANCES

4

NUMBER OF SOCKETS

1 socket for standard current circuit

VERSION

5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE

Suitable for fixing to furniture.

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195765

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.825

PRODUCT NET WEIGHT

0.825

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053195765

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

285

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3384375

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.825

PACKAGING WEIGHT UNIT

KGM